

## CONTROL UNIT FOR A CAPACITIVE ACTUATOR

**Publication number:** WO0133061

**Publication date:** 2001-05-10

**Inventor:** CHEMISKY ERIC (DE); KAPPEL ANDREAS (DE);  
GOTTLIEB BERNHARD (DE); BAUSEWEIN ANDREAS  
(DE); MEIXNER HANS (DE)

**Applicant:** SIEMENS AG (DE); CHEMISKY ERIC (DE); KAPPEL  
ANDREAS (DE); GOTTLIEB BERNHARD (DE);  
BAUSEWEIN ANDREAS (DE); MEIXNER HANS (DE)

**Classification:**

**- international:** F02D41/20; H01L41/04; H02N2/06; F02D41/20;  
H01L41/00; H02N2/02; (IPC1-7): F02D41/20;  
H01L41/04

**- european:** F02D41/20P; H01L41/04B

**Application number:** WO2000DE03863 20001103

**Priority number(s):** DE19991052950 19991103

**Also published as:**

EP1226348 (A1);  
EP1226348 (A0);  
DE19952950 (A);  
EP1226348 (B1);


**Cited documents:**

GB2334623  
US4749897  
JP2176121  
US5543679  
DE19734895  
more >>

**Report a data error he**

### Abstract of WO0133061

The invention relates to a capacitive actuator, especially a piezoactuator in a fuel injection device, which is controlled by means of an output stage that is embodied as a fly back converter having a transformer. A charging and/or discharging device comprising a switching transistor that is switched into a connecting state by means of a pulse-width modulated signal is provided. The pulse duty factor of the pulse-width modulated signal is determined in such a way that the transistor remains in the connecting state until a current value which is measured on the transistor matches a variable reference current value.



Data supplied from the esp@cenet database - Worldwide

**THIS PAGE BLANK (USPTO)**

Docket # 2004 P00792

Applic. # \_\_\_\_\_

Applicant: Augeskey

Lerner Greenberg Steiner LLP

Post Office Box 2480

Hollywood, FL 33022-2480

Tel: (954) 925-1100 Fax: (954) 925-1101